

**Garant**
**HSS-Co8 jobber drill, TiAlN, Ø DC h8: 6,9 mm**

**Order data**

Order number	114550 6,9
GTIN	4045197021182
Item class	11B

**Description**
**Version:**

**Extremely high heat resistance, very robust** due to **strong core**.

With point geometry shape C.

**Recommendation:**
**Maximum drilling depth:**

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 135 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth  $L_2$ : 58.7 mm

Flute length  $L_c$ : 69 mm

Overall length L: 109 mm

Shank Ø  $D_s$ : 6.9 mm

Feed f in stainless steel > 900 N/mm<sup>2</sup>: 0.05 mm/rev.

**Technical description**

Nominal Ø $D_c$	6.9 mm
Number of cutting edges Z	2
Feed f in stainless steel > 900 N/mm <sup>2</sup>	0.05 mm/rev.
Flute length $L_c$	69 mm
Tolerance nominal Ø	h8
Shank Ø $D_s$	6.9 mm

Overall length L	109 mm
Standard	DIN 338
recommended maximum drilling depth L <sub>2</sub>	58.7 mm
Point angle	135 degrees
Coating	TiAlN
Tool material	HSS Co 8
Helix angle	35 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	blue
Type of product	Jobber drill