

Garant
HSS-Co8 jobber drill, TiAlN, Ø DC h8: 9,8 mm

Order data

| | |
|--------------|---------------|
| Order number | 114550 9,8 |
| GTIN | 4045197021472 |
| Item class | 11B |

Description
Version:

Extremely high heat resistance, very robust due to **strong core**.

With point geometry shape C.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 135 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 72.3 mm

Flute length L_c : 87 mm

Overall length L: 133 mm

Shank Ø D_s : 9.8 mm

Feed f in stainless steel > 900 N/mm²: 0.09 mm/rev.

Technical description

| | |
|---|--------------|
| Flute length L_c | 87 mm |
| Nominal Ø D_c | 9.8 mm |
| Feed f in stainless steel > 900 N/mm ² | 0.09 mm/rev. |
| Number of cutting edges Z | 2 |
| Tolerance nominal Ø | h8 |
| Shank Ø D_s | 9.8 mm |

| | |
|---|--------------|
| Overall length L | 133 mm |
| Standard | DIN 338 |
| recommended maximum drilling depth L ₂ | 72.3 mm |
| Point angle | 135 degrees |
| Coating | TiAlN |
| Tool material | HSS Co 8 |
| Helix angle | 35 degrees |
| Shank | Plain shank |
| Through-coolant | no |
| Colour ring | blue |
| Type of product | Jobber drill |