

Garant
Jobber drill SS-E-PM HPC, TiAlN, Ø DC h8: 2,6 mm

Order data

Order number	114620 2,6
GTIN	4045197023551
Item class	11B

Description
Version:

Dimensions similar to DIN 338.

Shank to DIN 1835A.

High-performance HPC twist drills for high-alloy and high tensile materials. Particularly strong due to **strengthened core and a parabolic flute profile**. Point geometry with rake angle correction. Precise concentricity for exact holes.

With form S point.

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Machining strategy: HPC

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 26.1 mm

Flute length L_c : 30 mm

Overall length L: 62 mm

Shank Ø D_s : 3 mm

Feed f in steel < 900 N/mm²: 0.03 mm/rev.

Technical description

Flute length L_c	30 mm
Feed f in steel < 900 N/mm ²	0.03 mm/rev.
Number of cutting edges Z	2

Nominal $\varnothing D_c$	2.6 mm
Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	3 mm
Overall length L	62 mm
Standard	DIN 338
recommended maximum drilling depth L_2	26.1 mm
Point angle	130 degrees
Coating	TiAlN
Tool material	HSS E PM
Helix angle	38 degrees
Shank	DIN 1835 A to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill