



Jobber drill set HSS No. 114360 in a case, TiN, Type: 1-10,5



Order data

Order number	115245 1-10,5
GTIN	4045197024695
Item class	12B

Description

Version:

Composed of jobber drills DIN 338.
Standard core without core taper.
Precision ground point.

Profile ground:

High concentricity and pitch accuracy, drills for series production use.
With point geometry shape C from size 2.4 mm.

Through-coolant: no

Shank: Plain shank

Drill range: 1 - 10.5 mm

Number of drills: 24

Tapping hole Ø: 3.3; 4.2; 6.8; 10.2 mm

Incremental steps of drills: 0.5 mm

Technical description

Number of drills	24
Drill range	1 - 10.5 mm

Incremental steps of drills	0.5 mm
Shank	Plain shank
Tapping hole Ø	3.3; 4.2; 6.8; 10.2 mm
Number of cutting edges Z	2
Coating	TiN
Tool material	HSS
Standard	DIN 338
Type	N
Tolerance nominal Ø	h8
Point angle	118 degrees
Through-coolant	no
with case	yes
Colour ring	without
Type of product	Jobber drill

Accessories

Jobber drill HSS N Ø DC h8 2,5 mm	114360 2,5
Jobber drill HSS N Ø DC h8 1,5 mm	114360 1,5
Jobber drill HSS N Ø DC h8 3,5 mm	114360 3,5
Jobber drill HSS N Ø DC h8 7,5 mm	114360 7,5
Jobber drill HSS N Ø DC h8 10 mm	114360 10
Jobber drill HSS N Ø DC h8 1 mm	114360 1
Jobber drill HSS N Ø DC h8 8 mm	114360 8
Jobber drill HSS N Ø DC h8 5 mm	114360 5
Jobber drill HSS N Ø DC h8 5,5 mm	114360 5,5
Jobber drill HSS N Ø DC h8 9,5 mm	114360 9,5
Jobber drill HSS N Ø DC h8 9 mm	114360 9
Jobber drill HSS N Ø DC h8 6,8 mm	114360 6,8

Jobber drill HSS N Ø DC h8 2 mm	114360 2
Jobber drill HSS N Ø DC h8 3 mm	114360 3
Jobber drill HSS N Ø DC h8 7 mm	114360 7
Jobber drill HSS N Ø DC h8 6,5 mm	114360 6,5
Jobber drill HSS N Ø DC h8 4,5 mm	114360 4,5
Jobber drill HSS N Ø DC h8 8,5 mm	114360 8,5
Jobber drill HSS N Ø DC h8 4 mm	114360 4
Jobber drill HSS N Ø DC h8 3,3 mm	114360 3,3
Jobber drill HSS N Ø DC h8 10,5 mm	114360 10,5
Jobber drill HSS N Ø DC h8 10,2 mm	114360 10,2
Jobber drill HSS N Ø DC h8 6 mm	114360 6
Jobber drill HSS N Ø DC h8 4,2 mm	114360 4,2