

Garant

Jobber drill long HSS N, uncoated, Ø DC h8: 2,1 mm



Order data

Order number	116000 2,1
GTIN	4045197025234
Item class	11B

Description

Version:

Vaporised from 2.4 mm. Particularly for deep hole drilling (for deep holes, repeated chip evacuation is necessary).

With point geometry shape A from size 4 mm.

Advantage:

Especially suitable for **long reach purposes**. (When used to drill deep holes, low feed rates and frequent drill pecks are necessary).

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 52.85 mm

Flute length L_c : 56 mm

Overall length L: 85 mm

Shank Ø D_s : 2.1 mm

Feed f in steel < 750 N/mm²: 0.02 mm/rev.

Technical description

Nominal Ø D_c	2.1 mm
-----------------	--------

Flute length L_c	56 mm
Feed f in steel $< 750 \text{ N/mm}^2$	0.02 mm/rev.
Number of cutting edges Z	2
Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	2.1 mm
Overall length L	85 mm
Standard	DIN 340
recommended maximum drilling depth L_2	52.85 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill