

Garant**Jobber drill long HSS N, uncoated, Ø DC h8: 7,2 mm****Order data**

Order number	116000 7,2
GTIN	4045197025555
Item class	11B

Description**Version:**

Vaporised from 2.4 mm. Particularly for deep hole drilling (for deep holes, repeated chip evacuation is necessary).

With point geometry shape A from size 4 mm.

Advantage:

Especially suitable for **long reach purposes**. (When used to drill deep holes, low feed rates and frequent drill pecks are necessary).

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 91.2 mm

Flute length L_c : 102 mm

Overall length L: 156 mm

Shank Ø D_s : 7.2 mm

Feed f in steel < 750 N/mm²: 0.05 mm/rev.

Technical description

Feed f in steel < 750 N/mm ²	0.05 mm/rev.
-----------------------------------------	--------------

Nominal Ø D _c	7.2 mm
Number of cutting edges Z	2
Flute length L _c	102 mm
Tolerance nominal Ø	h8
Shank Ø D _s	7.2 mm
Overall length L	156 mm
Standard	DIN 340
recommended maximum drilling depth L ₂	91.2 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill