

Jobber drill long HSS W, uncoated, Ø DC h8: 2,5 mm



Order data

Order number	116040 2,5
GTIN	4045197025746
Item class	11B

Description

Version:

With point geometry shape A from size 2.5 mm.

Strengthened core **without core taper.** Precision ground point. Wide flutes with heavily honed back edges. Bright ground surface finish.

Advantage:

For deep hole drilling and for use with drill bushings.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Suitable NC spotting drills No. 112120, 112140 and 112170 with **142° tip angle** for enhanced process reliability.

Through-coolant: no Standard: DIN 340

Tolerance nominal Ø: h8 Point angle: 130 degrees Number of cutting edges Z: 2

recommended maximum drilling depth L₂: 58.25 mm

Flute length L_c: 62 mm Overall length L: 95 mm Shank \varnothing D_s: 2.5 mm

Feed f in aluminium short-chipping: 0.05 mm/rev.

Technical description

Nominal Ø D _c	2.5 mm
Number of cutting edges Z	2

Feed f in aluminium short-chipping	0.05 mm/rev.
Flute length L _c	62 mm
Tolerance nominal Ø	h8
Shank Ø D _s	2.5 mm
Overall length L	95 mm
Standard	DIN 340
recommended maximum drilling depth L ₂	58.25 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS
Туре	W
Helix angle	30-40 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	yellow
Type of product	Jobber drill