

Garant

Jobber drill long HSS W, uncoated, Ø DC h8: 7,5 mm



Order data

Order number	116040 7,5
GTIN	4045197025876
Item class	11B

Description

Version:

With point geometry shape A from size 2.5 mm.

Strengthened core **without core taper**. Precision ground point. Wide flutes with heavily honed back edges. Bright ground surface finish.

Advantage:

For deep hole drilling and for use with drill bushings.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Suitable NC spotting drills No. 112120, 112140 and 112170 with **142° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L₂: 90.75 mm

Flute length L_c: 102 mm

Overall length L: 156 mm

Shank Ø D_s: 7.5 mm

Feed f in aluminium short-chipping: 0.14 mm/rev.

Technical description

Flute length L _c	102 mm
Number of cutting edges Z	2

Feed f in aluminium short-chipping	0.14 mm/rev.
Nominal $\varnothing D_c$	7.5 mm
Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	7.5 mm
Overall length L	156 mm
Standard	DIN 340
recommended maximum drilling depth L_2	90.75 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS
Type	W
Helix angle	30-40 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	yellow
Type of product	Jobber drill