

**Garant**
**Deep hole drill HSS-E, uncoated, Ø DC h8: 10,5 mm**

**Order data**

Order number	116061 10,5
GTIN	4045197027023
Item class	11B

**Description**
**Version:**

Significantly **strengthened core** without taper.

Precision ground point.

With **specialty shaped slots**. Designed for deep holes up to 10×D and materials with critical chip formation characteristics.

**Recommendation:**
**Maximum drilling depth:**

flute length (see table) less 1.5×nominal Ø.

**Note:**

Suitable NC spotting drills No. 112120, 112140 and 112170 with **142° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L<sub>2</sub>: 105.3 mm

Flute length L<sub>c</sub>: 121 mm

Overall length L: 184 mm

Shank Ø D<sub>s</sub>: 10.5 mm

Feed f in steel < 500 N/mm<sup>2</sup>: 0.2 mm/rev.

**Technical description**

Flute length L <sub>c</sub>	121 mm
Nominal Ø D <sub>c</sub>	10.5 mm
Feed f in steel < 500 N/mm <sup>2</sup>	0.2 mm/rev.

Number of cutting edges Z	2
Tolerance nominal $\varnothing$	h8
Shank $\varnothing D_s$	10.5 mm
Overall length L	184 mm
Standard	DIN 340
recommended maximum drilling depth $L_2$	105.3 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	FS
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill