

Garant
Deep hole drill HSS-E, uncoated, Ø DC h8: 5 mm

Order data

Order number	116061 5
GTIN	4045197026828
Item class	11B

Description
Version:

Significantly **strengthened core** without taper.

Precision ground point.

With **specially shaped slots**. Designed for deep holes up to 10×D and materials with critical chip formation characteristics.

Recommendation:
Maximum drilling depth:

$$L_2 = L_C - 1.5 \times D_C$$

Note:

Suitable NC spotting drills No. 112120, 112140 and 112170 with **142° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 79.5 mm

Flute length L_C : 87 mm

Overall length L: 132 mm

Shank Ø D_s : 5 mm

Feed f in steel < 500 N/mm²: 0.05 mm/rev.

Technical description

Nominal Ø D_C	5 mm
Number of cutting edges Z	2
Feed f in steel < 500 N/mm ²	0.05 mm/rev.

Flute length L_c	87 mm
Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	5 mm
Overall length L	132 mm
Standard	DIN 340
recommended maximum drilling depth L_2	79.5 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	FS
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill