

## Garant

### Deep hole drill HSS-E, uncoated, Ø DC h8: 6,5 mm



#### Order data

Order number	116061 6,5
GTIN	4045197026880
Item class	11B

#### Description

##### Version:

Significantly **strengthened core** without taper.

Precision ground point.

With **specially shaped slots**. Designed for deep holes up to 10×D and materials with critical chip formation characteristics.

##### Recommendation:

##### Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c.$$

##### Note:

Suitable NC spotting drills No. 112120, 112140 and 112170 with **142° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth  $L_2$ : 87.3 mm

Flute length  $L_c$ : 97 mm

Overall length L: 148 mm

Shank Ø  $D_s$ : 6.5 mm

Feed f in steel < 500 N/mm<sup>2</sup>: 0.12 mm/rev.

#### Technical description

Feed f in steel < 500 N/mm <sup>2</sup>	0.12 mm/rev.
Nominal Ø $D_c$	6.5 mm
Number of cutting edges Z	2

Flute length $L_c$	97 mm
Tolerance nominal $\varnothing$	h8
Shank $\varnothing D_s$	6.5 mm
Overall length L	148 mm
Standard	DIN 340
recommended maximum drilling depth $L_2$	87.3 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	FS
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill