

**Garant**
**Jobber drill, long, HSS-E N, uncoated, Ø DC h8: 5,8 mm**

**Order data**

Order number	116065 5,8
GTIN	4045197270641
Item class	11B

**Description**
**Version:**

Profile ground. Standard core thickness and core taper. Bright finish.  
With point geometry shape AC from 2 mm.

**Advantage:**

For drilling with drill bushes or long reach applications.  
For high-tensile tempered steels, **including TOOLOX**.

**Recommendation:**
**Maximum drilling depth:**

$$L_2 = L_c - 1.5 \times D_c.$$

**Note:**

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth  $L_2$ : 82.3 mm

Flute length  $L_c$ : 91 mm

Overall length L: 139 mm

Shank Ø  $D_s$ : 5.8 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.05 mm/rev.

**Technical description**

Number of cutting edges Z	2
Feed f in steel < 1100 N/mm <sup>2</sup>	0.05 mm/rev.

Nominal $\varnothing D_c$	5.8 mm
Flute length $L_c$	91 mm
Tolerance nominal $\varnothing$	h8
Shank $\varnothing D_s$	5.8 mm
Overall length L	139 mm
Standard	DIN 340
recommended maximum drilling depth $L_2$	82.3 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS E
Type	N
Helix angle	35-40 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	red
Type of product	Jobber drill