

Garant
Jobber drill, long, HSS-E VA, uncoated, Ø DC h8: 11,8 mm

Order data

Order number	116070 11,8
GTIN	4045197028068
Item class	11B

Description
Version:

Profile ground. Standard core thickness and core taper. Bright finish.
With point geometry shape C.

Advantage:

For drilling with drill bushes or long reach applications.

Recommendation:
Maximum drilling depth:

$$L_2 = L_C - 1.5 \times D_C$$

Note:

Suitable NC spotting drills No. 112120, 112140 and 112170 with **142° tip angle** for enhanced process reliability.

Through-coolant: no

Standard: DIN 340

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 110.3 mm

Flute length L_C : 128 mm

Overall length L: 195 mm

Shank Ø D_s : 11.8 mm

Feed f in stainless steel < 900 N/mm²: 0.08 mm/rev.

Technical description

Number of cutting edges Z	2
Feed f in stainless steel < 900 N/mm ²	0.08 mm/rev.
Nominal Ø D_C	11.8 mm

Flute length L_c	128 mm
Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	11.8 mm
Overall length L	195 mm
Standard	DIN 340
recommended maximum drilling depth L_2	110.3 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Helix angle	35-40 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	blue
Type of product	Jobber drill