

Garant
Jobber drill extra long HSS FS, uncoated, Ø DC h8 × overall length L: 8X390 mm

Order data

Order number	116240 8X390
GTIN	4045197028877
Item class	11B

Description
Version:

With precision ground point.

Significantly strengthened core without core taper. Bright finish flutes, nitrided chamfers.

With point geometry shape C.

Advantage:

Special deep hole drills. For particularly deep or recessed holes. Good chip evacuation due to parabolic flutes, resulting in fewer chip evacuations even in particularly deep holes.

Recommendation:

Maximum drilling depth:

Flute length L_c (see table) less $1.5 \times \varnothing D_c$.

Note:

Suitable NC spotting drills No. 112120, 112140 and 112170 with **142° tip angle** for enhanced process reliability

Through-coolant: no

Standard: DIN 1869

Tolerance nominal \varnothing : h8

Point angle: 130 degrees

Number of cutting edges Z: 2

Flute length L_c : 265 mm

Overall length L: 390 mm

Shank $\varnothing D_s$: 8 mm

Feed f in steel < 750 N/mm^2 : 0.1 mm/rev.

Technical description

Flute length L_c	265 mm
--------------------	--------

Feed f in steel < 750 N/mm ²	0.1 mm/rev.
Number of cutting edges Z	2
Nominal \varnothing D _c	8 mm
Tolerance nominal \varnothing	h8
Shank \varnothing D _s	8 mm
Overall length L	390 mm
Standard	DIN 1869
Point angle	130 degrees
Coating	uncoated
Tool material	HSS
Type	FS
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill