

Garant

Jobber drill extra long HSS N, uncoated, Ø DC h8 × overall length L: 2,5X225 mm



Order data

| | |
|--------------|----------------|
| Order number | 116245 2,5X225 |
| GTIN | 4045197745668 |
| Item class | 11B |

Description

Version:

With precision ground point.

Vaporised high performance drills for drilling particularly deep holes. Take particular care to ensure **frequent chip clearance**.

Recommendation:

Maximum drilling depth:

Flute length L_c (see table) less $1.5 \times \varnothing D_c$.

Note:

Suitable NC spotting drills No. 112103, 112110 and 112160 with **120° tip angle** for enhanced process reliability

Through-coolant: no

Standard: DIN 1869

Tolerance nominal \varnothing : h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 150 mm

Overall length L: 225 mm

Shank $\varnothing D_s$: 2.5 mm

Feed f in steel < 750 N/mm^2 : 0.05 mm/rev.

Technical description

| | |
|---------------------------|----------|
| Standard | DIN 1869 |
| Number of cutting edges Z | 2 |
| Overall length L | 225 mm |

| | |
|---|--------------|
| Shank $\varnothing D_s$ | 2.5 mm |
| Tolerance nominal \varnothing | h8 |
| Feed f in steel < 750 N/mm ² | 0.05 mm/rev. |
| Nominal $\varnothing D_c$ | 2.5 mm |
| Flute length L_c | 150 mm |
| Point angle | 118 degrees |
| Coating | uncoated |
| Tool material | HSS |
| Type | N |
| Helix angle | 38 degrees |
| Shank | Plain shank |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Jobber drill |