

Garant
Straight shank taper pin drill, uncoated, Ø DC: 6 mm

Order data

Order number	116310 6
GTIN	4045197029362
Item class	11B

Description
Version:

Conically increasing cutting edges with chip breaker flutes on the circumference. Special surface treatment.

Advantage:

Conical holes 1:50 for taper pins to ISO 2339 (DIN 1) and ISO 8736 (DIN 7978) can be drilled in a single operation.

Note:

Ø1.5; 2; 2.5 available with plain shank on request.

Ø14;16; 20; 25 available with MT shank on request.

For finishing use taper pin reamers No. 161200.

Through-coolant: no

Standard: DIN 1898 A

Point angle: 118 degrees

Number of cutting edges Z: 2

smallest Ø D₁: 5.9 mm

largest Ø D₂: 8.23 mm

Taper lead length L₁: 5 mm

L₂: 105 mm

Overall length L: 160 mm

Shank Ø D_s: 8 mm

Technical description

Number of cutting edges Z	2
largest Ø D ₂	8.23 mm
Nominal Ø D _c	6 mm

Taper lead length L_1	5 mm
Feed f in steel $< 750 \text{ N/mm}^2$	0.05 mm/rev.
Shank $\varnothing D_s$	8 mm
Overall length L	160 mm
L_2	105 mm
smallest $\varnothing D_1$	5.9 mm
Standard	DIN 1898 A
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Taper ratio	1:50
Through-coolant	no
Colour ring	without
Type of product	Jobber drill