

**Garant**
**HSS jobber drill N, uncoated, Ø DC h8: 17 mm**

**Order data**

Order number	116340 17
GTIN	4045197030344
Item class	11C

**Description**
**Version:**

Special surface treatment, resulting in reduced tendency to edge build-up **and improved chip evacuation.**

**Top quality high performance twist drills.**

Cutting edge section ≤ 26.5 mm Ø ground from solid, > 26.5 mm Ø milled. This ensures high concentricity and pitch accuracy, and precision ground point up to 40 mm Ø.

With shape A point.

**Recommendation:**
**Maximum drilling depth:**

$$L_2 = L_c - 1.5 \times D_c.$$

**Note:**

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530.**

Through-coolant: no

Standard: DIN 345

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth  $L_2$ : 99.5 mm

Flute length  $L_c$ : 125 mm

Overall length L: 223 mm

Morse taper MT size: 2

Feed  $f$  in steel < 750 N/mm<sup>2</sup>: 0.2 mm/rev.

**Technical description**

Nominal Ø $D_c$	17 mm
Number of cutting edges Z	2

Flute length $L_c$	125 mm
Feed $f$ in steel $< 750 \text{ N/mm}^2$	0.2 mm/rev.
Tolerance nominal $\varnothing$	h8
Overall length $L$	223 mm
Morse taper MT size	2
Standard	DIN 345
recommended maximum drilling depth $L_2$	99.5 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	20-30 degrees
Shank	Morse taper
Through-coolant	no
Colour ring	without
Type of product	Jobber drill