

Garant
Jobber drill extra long HSS FS, uncoated, Ø DC h8: 12,5R2 mm

Order data

| | |
|--------------|---------------|
| Order number | 116720 12,5R2 |
| GTIN | 4045197034786 |
| Item class | 11C |

Description
Version:

High concentricity.

Large section parabolic flutes; strong due to strengthened core thickness (without core taper).

≤ 16 mm Ø: Bright finish flutes, nitrided lands; > 16 mm Ø: Specially treated surface.

Special sturdy drills **for extremely deep holes.** Up to approx. 15×Ø without drill withdrawal.

With point geometry shape A.

Note:

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530.**

Through-coolant: no

Standard: DIN 1870 R2

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

Flute length L_c : 260 mm

Overall length L: 395 mm

Morse taper MT size: 1

Feed f in steel < 750 N/mm²: 0.16 mm/rev.

Technical description

| | |
|---|--------------|
| Feed f in steel < 750 N/mm ² | 0.16 mm/rev. |
| Nominal Ø D_c | 12.5 mm |
| Number of cutting edges Z | 2 |
| Flute length L_c | 260 mm |
| Tolerance nominal Ø | h8 |

| | |
|---------------------|--------------|
| Overall length L | 395 mm |
| Morse taper MT size | 1 |
| Standard | DIN 1870 R2 |
| Point angle | 130 degrees |
| Coating | uncoated |
| Tool material | HSS |
| Type | FS |
| Shank | Morse taper |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Jobber drill |