

**Garant**
**Jobber drill extra long HSS N, uncoated, Ø DC h8: 12R2 mm**

**Order data**

Order number	116760 12R2
GTIN	4045197035288
Item class	11C

**Description**
**Version:**

High concentricity. Core thickness and core taper are standard.

Special surface treatment.

Precision ground point. When drilling deep holes, evacuate chips from the hole frequently, and ensure adequate cooling.

Economy version with standard flutes.

With point geometry shape A.

**Note:**

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Through-coolant: no

Standard: DIN 1870 R2

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length  $L_c$ : 260 mm

Overall length L: 395 mm

Morse taper MT size: 1

Feed f in steel < 750 N/mm<sup>2</sup>: 0.16 mm/rev.

**Technical description**

Feed f in steel < 750 N/mm <sup>2</sup>	0.16 mm/rev.
Nominal Ø $D_c$	12 mm
Number of cutting edges Z	2
Flute length $L_c$	260 mm
Tolerance nominal Ø	h8

Overall length L	395 mm
Morse taper MT size	1
Standard	DIN 1870 R2
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	16-30 degrees
Shank	Morse taper
Through-coolant	no
Colour ring	without
Type of product	Jobber drill