

Garant
Jobber drill extra long HSS N, uncoated, Ø DC h8: 13R1 mm

Order data

Order number	116760 13R1
GTIN	4045197035301
Item class	11C

Description
Version:

High concentricity. Core thickness and core taper are standard.

Special surface treatment.

Precision ground point. When drilling deep holes, evacuate chips from the hole frequently, and ensure adequate cooling.

Economy version with standard flutes.

With point geometry shape A.

Note:

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Through-coolant: no

Standard: DIN 1870 R1

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Flute length L_c : 205 mm

Overall length L: 310 mm

Morse taper MT size: 1

Feed f in steel < 750 N/mm²: 0.16 mm/rev.

Technical description

Nominal Ø D_c	13 mm
Feed f in steel < 750 N/mm ²	0.16 mm/rev.
Flute length L_c	205 mm
Number of cutting edges Z	2
Tolerance nominal Ø	h8

Overall length L	310 mm
Morse taper MT size	1
Standard	DIN 1870 R1
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Helix angle	16-30 degrees
Shank	Morse taper
Through-coolant	no
Colour ring	without
Type of product	Jobber drill