

Garant
Stub subland drill HSS 90°, TiAlN, for screws: M3

Order data

Order number	117140 M3
GTIN	4045197035950
Item class	11C

Description
Version:

Very sturdy. Tight concentricity tolerances between drill \varnothing and counterbore \varnothing guarantee exact alignment.

Application:

Particularly suitable for NC machines due to high positional accuracy, excellent centring properties and great sturdiness. The preceding centring operation can thus often be omitted. For through holes for screws to DIN-ISO 273 and countersinks to DIN 74, sheet 1 form A, fine version.

For screws to ISO 2009, 2010, 7046, 7047 (DIN 963, 964, 965 and 966).

$\varnothing D_1$ 1st step with chamfer h8: 3.2 mm

$\varnothing D_2$ 2nd step with chamfer h8: 6 mm

Step height L_1 1st step: 9 mm

Flute length L_c : 28 mm

Overall length L: 66 mm

Shank $\varnothing D_s$: 6 mm

Technical description

$\varnothing D_2$ 2nd step with chamfer h8	6 mm
Feed f in steel < 750 N/mm ²	0.03 mm/rev.
for screws	M3
$\varnothing D_1$ 1st step with chamfer h8	3.2 mm
Flute length L_c	28 mm
Number of cutting edges Z	2

Shank $\varnothing D_s$	6 mm
Overall length L	66 mm
Step height L_1 1st step	9 mm
Coating	TiAlN
Tool material	HSS
Standard	DIN 1897
Tolerance nominal \varnothing	h8
Point angle	118 degrees
Shank	Parallel shank to h8
Countersink angle	90 degrees
Through-coolant	no
Shank tolerance	h8
Colour ring	without
Type of product	Stepped drill