

Garant
Stub subland drill HSS 180°, TiAlN, for screws: M6

Order data

Order number	117260 M6
GTIN	4045197036254
Item class	11C

Description
Version:

Very sturdy. Tight concentricity tolerances between drill \varnothing and counterbore \varnothing guarantee exact alignment.

Application:

For through holes for screws to DIN-ISO 273 and countersinking to DIN 74, sheet 2 form H, J and K, medium version.

For screws to DIN 912, 6912 and 7984, ISO 1207 (DIN 84).

$\varnothing D_1$ 1st step 180° h8: 6.6 mm

$\varnothing D_2$ 2nd step 180° h8: 11 mm

Step height L_1 1st step 180°: 15 mm

Flute length L_c : 47 mm

Overall length L: 95 mm

Shank $\varnothing D_s$: 11 mm

Technical description

Number of cutting edges Z	2
Feed f in steel < 750 N/mm ²	0.07 mm/rev.
$\varnothing D_2$ 2nd step 180° h8	11 mm
$\varnothing D_1$ 1st step 180° h8	6.6 mm
for screws	M6
Flute length L_c	47 mm
Step height L_1 1st step 180°	15 mm

Shank $\varnothing D_s$	11 mm
Overall length L	95 mm
Coating	TiAlN
Tool material	HSS
Standard	DIN 1897
Tolerance nominal \varnothing	h8
Point angle	118 degrees
Shank	Parallel shank to h8
Countersink angle	180 degrees
Through-coolant	no
Shank tolerance	h8
Colour ring	without
Type of product	Stepped drill