

Garant
Carbide hole saw high, Ø DC: 43 mm

Order data

| | |
|--------------|---------------|
| Order number | 118400 43 |
| GTIN | 4045197036971 |
| Item class | 11C |

Description
Version:

Extremely strong and with perfect concentricity due to **drill crown and shank of one piece** (hardened).

Narrow carbide cutting edges with **positive rake** and **large clearance angle** provide good cutting performance at low cutting pressure.

Exchangeable centre drill, shank with 3 clamping faces.

Cutting width 2 mm for all sizes. Ø tolerance: + **0.10** / – **0.05 mm**.

Dimension L: **size ≤ 55 = 35 mm / size 60 = 60 mm**.

Application:

For use on stationary machines. Suitable for fibre-reinforced plastics (GRP and CRP).

For flat material up to 4 mm thickness, and pipes of up to 4 mm wall thickness.

Ø tolerance: –0.05 / 0.1 mm

Shank Ø: 10 mm

Length L: 35 mm

Technical description

| | |
|--------------------------|-------------------------|
| Nominal Ø D _c | 43 mm |
| Shank Ø | 10 mm |
| Length L | 35 mm |
| Version | high |
| Tool material | Carbide |
| Standard | Manufacturer's standard |

| | |
|-----------------|-------------------------|
| Shank | Three drive flats shank |
| Ø tolerance | -0.05 / 0.1 mm |
| Colour ring | without |
| Type of product | Hole saw |