

## Garant

### Carbide core drill Depth of cut 30 mm, TiAlN, Ø DC: 14 mm



#### Order data

|              |               |
|--------------|---------------|
| Order number | 118780 14     |
| GTIN         | 4045197514608 |
| Item class   | 11F           |

#### Description

##### Version:

Suitable for all popular magnetic core drilling machines. Very good cutting properties due to optimised cutting edge geometry. Easy to regrind. With Weldon shank - Ø **19 mm**.

**Carbide with special TiAlN coating** – long tool life and outstanding cutting performance.

##### Application:

On mobile magnetic drilling machines or stationary pillar drilling machines to produce large holes in steel construction. The core drill cuts only a thin material ring. The drilled core is ejected by a spring loaded ejector pin.

##### Supplied with:

**Without** ejector pin.

##### Note:

- **Larger sizes, intermediate sizes, and HSS core drills with 110 mm cutting depth available on request.**
- **For the lubrication of core drills, we recommend high performance cutting oil (see No. 084210).**

Standard: Manufacturer's standard

#### Technical description

|                          |                         |
|--------------------------|-------------------------|
| Nominal Ø D <sub>c</sub> | 14 mm                   |
| Coating                  | TiAlN                   |
| Tool material            | Carbide                 |
| Standard                 | Manufacturer's standard |
| Colour ring              | without                 |

Type of product

Hole saw