

Garant
Carbide tipped jobber drill, uncoated, Ø DC h8: 8 mm

Order data

| | |
|--------------|---------------|
| Order number | 121150 8 |
| GTIN | 4045197471420 |
| Item class | 11E |

Description
Version:

With carbide cutting tip. Ground between centres.
Shank with driver tang for use in clamping collets.

Recommendation:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Through-coolant: no

Standard: DIN 8037

Tolerance nominal Ø: h8

Number of cutting edges Z: 2

Tolerance nominal Ø: h8

recommended maximum drilling depth L_2 : 28 mm

Overall length L: 80 mm

Feed f in steel < 1100 N/mm²: 0.1 mm/rev.

Technical description

| | |
|--|-------------|
| Number of cutting edges Z | 2 |
| Feed f in steel < 1100 N/mm ² | 0.1 mm/rev. |
| Nominal Ø D_c | 8 mm |
| Flute length L_c | 40 mm |
| Tolerance nominal Ø | h8 |
| Overall length L | 80 mm |

| | |
|---|--------------|
| Standard | DIN 8037 |
| recommended maximum drilling depth L ₂ | 28 mm |
| Coating | uncoated |
| Tool material | Carbide K20 |
| Point angle | 118 degrees |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Jobber drill |