

Garant

Solid carbide special drill DIN 6535 HA, uncoated, Ø DC ±0.003: 11,98 mm



Order data

Order number	121201 11,98
GTIN	4045197857866
Item class	11E

Description

Version:

Spiral flute precision drill for plastics. **Self-centring** with **1-cutter geometry**, achieves **very high alignment accuracy**. **Polished** helical flutes for **optimum chip evacuation**.

Maintains the **tolerance band IT7** from entry Ø through to exit Ø, **due to special point geometry**.

Recommendation:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No.121201 + 129100HB**.

Form **HE**: order with **No.121201 + 129100HE**.

Semi-Standard: yes

Standard: Manufacturer's standard

Tolerance nominal Ø: ±0.003

Number of cutting edges Z: 1

Tolerance nominal Ø: ±0.003

recommended maximum drilling depth L_2 : 53.1 mm

Overall length L: 118 mm

Shank Ø D_s : 12 mm

Feed f in PEEK: 0.25 mm/rev.

Technical description

Flute length L_c	71 mm
Nominal Ø D_c	11.98 mm

recommended maximum drilling depth L_2	53.1 mm
Standard	Manufacturer's standard
Feed f in PEEK	0.25 mm/rev.
Shank $\varnothing D_s$	12 mm
Number of cutting edges Z	1
Overall length L	118 mm
Tolerance nominal \varnothing	± 0.003
Coating	uncoated
Tool material	Solid carbide
Drill depth up to	5×D
Point angle	120 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Semi-Standard	yes
Colour ring	without
Type of product	Jobber drill

Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE