

## Garant

**Solid carbide special drill DIN 6535 HA, uncoated, Ø DC ±0.003: 5,03 mm**



### Order data

Order number	121201 5,03
GTIN	4045197715722
Item class	11E

### Description

#### Version:

**Spiral flute** precision drill for plastics. **Self-centring** with **1-cutter geometry**, achieves **very high alignment accuracy**. **Polished** helical flutes for **optimum chip evacuation**.

**Maintains** the **tolerance band IT7** from entry Ø through to exit Ø, **due to special point geometry**.

#### Recommendation:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No.121201 + 129100HB**.

Form **HE**: order with **No.121201 + 129100HE**.

Semi-Standard: yes

Standard: Manufacturer's standard

Tolerance nominal Ø: ±0.003

Number of cutting edges Z: 1

Tolerance nominal Ø: ±0.003

recommended maximum drilling depth  $L_2$ : 36.5 mm

Overall length L: 82 mm

Shank Ø  $D_s$ : 6 mm

Feed f in PEEK: 0.15 mm/rev.

### Technical description

Flute length $L_c$	44 mm
Shank tolerance	h6

Nominal $\varnothing D_c$	5.03 mm
Number of cutting edges Z	1
Tolerance nominal $\varnothing$	$\pm 0.003$
Shank $\varnothing D_s$	6 mm
Overall length L	82 mm
Feed f in PEEK	0.15 mm/rev.
Standard	Manufacturer's standard
recommended maximum drilling depth $L_2$	36.5 mm
Coating	uncoated
Tool material	Solid carbide
Drill depth up to	5xD
Point angle	120 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Semi-Standard	yes
Colour ring	without
Type of product	Jobber drill

## Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE