

Garant
Solid carbide drill for aramide, uncoated, Ø DC h6: 7 mm

Order data

Order number	121230 7
GTIN	4045197472038
Item class	11Y

Description
Version:

Special geometry for reliable drilling of aramide plastics (polyaramides) and aramide fibres as well as thermoplastics and thermosetting plastics.

Recommendation:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Through-coolant: no

Standard: Manufacturer's standard

Tolerance nominal Ø: h6

Number of cutting edges Z: 2

Tolerance nominal Ø: h6

recommended maximum drilling depth L_2 : 23.5 mm

Overall length L: 74 mm

Shank Ø D_s : 7 mm

Feed f in AFK: 0.07 mm/rev.

Technical description

Nominal Ø D_c	7 mm
Shank tolerance	h6
Flute length L_c	34 mm
Feed f in AFK	0.07 mm/rev.
Number of cutting edges Z	2
Tolerance nominal Ø	h6

Shank $\varnothing D_s$	7 mm
Overall length L	74 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L_2	23.5 mm
Coating	uncoated
Tool material	Solid carbide
Drill depth up to	4xD
Shank	Parallel shank to h6
Use for drilling	for aramides
Through-coolant	no
Colour ring	without
Type of product	Jobber drill