

Garant

Solid carbide jobber drill extra stub, TiAlN, Ø DC h7: 7,3 mm



Order data

Order number	122151 7,3
GTIN	4045197748621
Item class	11E

Description

Version:

Similar to DIN 6539 (stub).

Nominal Ø and shank Ø equal.

TiAlN coating for even better performance.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Non slip clamping in drill chuck No. 341050 with diamond coated jaws.

Through-coolant: no

Standard: DIN 6539

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 23.1 mm

Overall length L: 74 mm

Shank Ø D_s : 7.3 mm

Feed f in steel < 1100 N/mm²: 0.11 mm/rev.

Technical description

Nominal Ø D_c	7.3 mm
Feed f in steel < 1100 N/mm ²	0.11 mm/rev.
Number of cutting edges Z	2
Shank tolerance	h7

Shank $\varnothing D_s$	7.3 mm
Overall length L	74 mm
Tolerance nominal \varnothing	h7
Flute length L_c	34 mm
Standard	DIN 6539
recommended maximum drilling depth L_2	23.1 mm
Coating	TiAlN
Tool material	solid carbide
Type	N
Point angle	118 degrees
Helix angle	30 degrees
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	Jobber drill