


Solid carbide jobber drill extra stub, TiN, Ø DC h7: 6,2 mm

Order data

Order number	122160 6,2
GTIN	4045197040695
Item class	12E

Description
Version:

Similar to DIN 6539 (stub).

Nominal Ø and shank Ø equal.

TiN coating.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Non slip clamping in drill chuck No. 341050 with diamond coated jaws.

Through-coolant: no

Standard: DIN 6539

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 21.7 mm

Overall length L: 70 mm

Shank Ø D_s : 6.2 mm

Feed f in steel < 1100 N/mm²: 0.11 mm/rev.

Technical description

Feed f in steel < 1100 N/mm ²	0.11 mm/rev.
Nominal Ø D_c	6.2 mm
Number of cutting edges Z	2
Flute length L_c	31 mm

Shank tolerance	h7
Tolerance nominal \varnothing	h7
Shank $\varnothing D_s$	6.2 mm
Overall length L	70 mm
Standard	DIN 6539
recommended maximum drilling depth L_2	21.7 mm
Coating	TiN
Tool material	Solid carbide
Type	N
Point angle	118 degrees
Helix angle	30 degrees
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	Jobber drill