

**Garant**
**Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 4,1 mm**

**Order data**

Order number	122307 4,1
GTIN	4045197756558
Item class	11E

**Description**
**Version:**

**DLC coating sp<sup>2</sup>** of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of aluminium materials. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

**Recommendation:**
**Maximum drilling depth:**

clamping slot length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 17.9 mm

Overall length L: 66 mm

Shank Ø  $D_s$ : 6 mm

Feed f in aluminium short-chipping: 0.35 mm/rev.

**Technical description**

Tolerance nominal Ø	h7
Nominal Ø $D_c$	4.1 mm
Overall length L	66 mm
Flute length $L_c$	24 mm
Standard	DIN 6537 K

Feed f in aluminium short-chipping	0.35 mm/rev.
Shank tolerance	h6
Shank $\varnothing D_s$	6 mm
Number of cutting edges Z	2
recommended maximum drilling depth $L_2$	17.9 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	4xD
Type	W
Point angle	135 degrees
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill