

**HOLEX**
**Solid carbide high performance drill, Whistle-Notch shank DIN 6535 HE, TiN,  
 Ø DC h7: 12,8 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 122320 12,8   |
| GTIN         | 4045197391209 |
| Item class   | 12E           |

**Description**
**Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

**Recommendation:**
**Maximum drilling depth:**

Flute length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

**NEW GENERATION AVAILABLE!**

**Recommended successor product is No. 122503.**

Through-coolant: no

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 40.8 mm

Overall length L: 107 mm

Shank Ø  $D_s$ : 14 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.26 mm/rev.

**Technical description**

|   |              |
|---|--------------|
| Flute length $L_c$                      | 60 mm        |
| Feed f in steel < 900 N/mm <sup>2</sup> | 0.26 mm/rev. |

|  |                   |
|--|-------------------|
| Nominal $\varnothing D_c$                | 12.8 mm           |
| Number of cutting edges Z                | 2                 |
| Shank tolerance                          | h6                |
| Tolerance nominal $\varnothing$          | h7                |
| Shank $\varnothing D_s$                  | 14 mm             |
| Overall length L                         | 107 mm            |
| Standard                                 | DIN 6537 K        |
| recommended maximum drilling depth $L_2$ | 40.8 mm           |
| Coating                                  | TiN               |
| Tool material                            | Solid carbide     |
| Drill depth up to                        | 4xD               |
| Point angle                              | 140 degrees       |
| Shank                                    | DIN 6535 HE to h6 |
| Through-coolant                          | no                |
| Colour ring                              | without           |
| Type of product                          | Jobber drill      |