

Garant
**Diabolo solid carbide HPC drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7:
14,5 mm**

Order data

Order number	122362 14,5
GTIN	4045197971333
Item class	11E

Description
Version:

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

Special multi-nano layer coating for drilling in hardened steels.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 43.3 mm

Overall length L: 115 mm

Shank Ø D_s : 16 mm

Feed f in steel < 60 HRC: 0.13 mm/rev.

Technical description

Tolerance nominal Ø	h7
Flute length L_c	65 mm
recommended maximum drilling depth L_2	43.3 mm
Overall length L	115 mm
Number of cutting edges Z	2
Feed f in steel < 60 HRC	0.13 mm/rev.

Nominal $\varnothing D_c$	14.5 mm
Standard	DIN 6537 K
Shank $\varnothing D_s$	16 mm
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Type	H
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	no
Machining strategy	HPC
Semi-Standard	yes
Colour ring	red
Type of product	Jobber drill