

Garant

Diabolo solid carbide HPC drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7 (mm or inch): 2,4 mm or inch



Order data

Order number	122371 2,4
GTIN	4045197968920
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

Special multi-nano layer coating for drilling in hardened steels.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \varnothing$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122362 / 122372**.

Form **HE**: order with **No. 122361 / 122371 + 129100HE**.

Standard: DIN 6537 K

Tolerance nominal \varnothing : h7

Number of cutting edges Z: 2

Tolerance nominal \varnothing : h7

recommended maximum drilling depth L_2 : 16.4 mm

Overall length L: 55 mm

Shank $\varnothing D_s$: 4 mm

Feed f in steel < 60 HRC: 0.02 mm/rev.

Technical description

recommended maximum drilling depth L_2	16.4 mm
Flute length L_c	20 mm

Number of cutting edges Z	2
Tolerance nominal \varnothing	h7
Overall length L	55 mm
Standard	DIN 6537 K
Feed f in steel < 60 HRC	0.02 mm/rev.
Shank $\varnothing D_s$	4 mm
Nominal $\varnothing D_c$	2.4 mm
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Type	H
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	red
Type of product	Jobber drill