

## Garant

### Diabolo solid carbide HPC drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 3,3 mm



#### Order data

Order number	122372 3,3
GTIN	4045197971425
Item class	11E

#### Description

##### Version:

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

**Special multi-nano layer coating** for drilling in hardened steels.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 15.1 mm

Overall length L: 62 mm

Shank Ø  $D_s$ : 6 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.11 mm/rev.

Feed f in steel < 60 HRC: 0.03 mm/rev.

#### Technical description

Feed f in steel < 60 HRC	0.03 mm/rev.
Overall length L	62 mm
recommended maximum drilling depth $L_2$	15.1 mm
Standard	DIN 6537 K
Number of cutting edges Z	2

Tolerance nominal $\varnothing$	h7
Shank $\varnothing D_s$	6 mm
Nominal $\varnothing D_c$	3.3 mm
Feed f in steel < 1100 N/mm <sup>2</sup>	0.11 mm/rev.
Flute length $L_c$	20 mm
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Type	H
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	red
Type of product	Jobber drill