

**Garant**
**Diabolo solid carbide HPC drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 5 mm**

**Order data**

Order number	122372 5
GTIN	4045197971494
Item class	11E

**Description**
**Version:**

Cutting chisel edge with **high centring accuracy** due to strong core and special point geometry. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

**Special multi-nano layer coating** for drilling in hardened steels.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 20.5 mm

Overall length L: 66 mm

Shank Ø  $D_s$ : 6 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.15 mm/rev.

Feed f in steel < 60 HRC: 0.04 mm/rev.

**Technical description**

Flute length $L_c$	28 mm
recommended maximum drilling depth $L_2$	20.5 mm
Shank Ø $D_s$	6 mm
Feed f in steel < 60 HRC	0.04 mm/rev.
Overall length L	66 mm

Feed f in steel < 1100 N/mm <sup>2</sup>	0.15 mm/rev.
Tolerance nominal Ø	h7
Nominal Ø D <sub>c</sub>	5 mm
Standard	DIN 6537 K
Number of cutting edges Z	2
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Type	H
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	red
Type of product	Jobber drill