



## Solid carbide high performance drill plain shank DIN 6535 HA, TiAlN, Ø DC m7: 16,5 mm



### Order data

Order number	122394 16,5
GTIN	4045197419859
Item class	12E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

#### Recommendation:

##### Maximum drilling depth:

clamping slot length (see table) less  $1.5 \times \text{nominal } \varnothing$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122396**.

Form **HE**: order with **No. 122398**.

Through-coolant: no

Standard: DIN 6537 K

Tolerance nominal  $\varnothing$ : m7

Number of cutting edges Z: 2

Tolerance nominal  $\varnothing$ : m7

recommended maximum drilling depth  $L_2$ : 48.3 mm

Overall length L: 123 mm

Shank  $\varnothing D_s$ : 18 mm

Feed f in stainless steel  $< 900 \text{ N/mm}^2$ : 0.16 mm/rev.

### Technical description

Feed f in stainless steel $< 900 \text{ N/mm}^2$	0.16 mm/rev.
Flute length $L_c$	73 mm

Number of cutting edges Z	2
Shank tolerance	h6
Nominal $\varnothing D_c$	16.5 mm
Tolerance nominal $\varnothing$	m7
Shank $\varnothing D_s$	18 mm
Overall length L	123 mm
Standard	DIN 6537 K
recommended maximum drilling depth $L_2$	48.3 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	blue
Type of product	Jobber drill