



## Solid carbide high performance drill Whistle-Notch shank DIN 6535 HE, TiAlN, Ø DC m7: 15,5 mm



### Order data

Order number	122398 15,5
GTIN	4045197427236
Item class	12E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

#### Recommendation:

##### Maximum drilling depth:

clamping slot length (see table) less  $1.5 \times \text{nominal } \varnothing$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Through-coolant: no

Standard: DIN 6537 K

Tolerance nominal  $\varnothing$ : m7

Number of cutting edges Z: 2

Tolerance nominal  $\varnothing$ : m7

recommended maximum drilling depth  $L_2$ : 41.8 mm

Overall length L: 115 mm

Shank  $\varnothing D_s$ : 16 mm

Feed f in stainless steel  $< 900 \text{ N/mm}^2$ : 0.15 mm/rev.

### Technical description

Number of cutting edges Z	2
Shank tolerance	h6
Nominal $\varnothing D_c$	15.5 mm
Flute length $L_c$	65 mm

Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.15 mm/rev.
Tolerance nominal Ø	m7
Shank Ø D <sub>s</sub>	16 mm
Overall length L	115 mm
Standard	DIN 6537 K
recommended maximum drilling depth L <sub>2</sub>	41.8 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	no
Colour ring	blue
Type of product	Jobber drill