



## Solid carbide high performance drill Whistle-Notch shank DIN 6535 HE, TiAlN, Ø DC m7: 18,5 mm



### Order data

Order number	122398 18,5
GTIN	4045197427328
Item class	12E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

#### Recommendation:

##### Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Through-coolant: no

Standard: DIN 6537 K

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth  $L_2$ : 51.3 mm

Overall length L: 131 mm

Shank Ø  $D_s$ : 20 mm

Feed f in stainless steel < 900 N/mm<sup>2</sup>: 0.16 mm/rev.

### Technical description

Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.16 mm/rev.
Number of cutting edges Z	2
Flute length $L_c$	79 mm
Nominal Ø $D_c$	18.5 mm

Shank tolerance	h6
Tolerance nominal $\varnothing$	m7
Shank $\varnothing D_s$	20 mm
Overall length L	131 mm
Standard	DIN 6537 K
recommended maximum drilling depth $L_2$	51.3 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	no
Colour ring	blue
Type of product	Jobber drill