



Solid carbide high performance drill Whistle-Notch shank DIN 6535 HE, TiAlN, Ø DC m7: 19,3 mm



Order data

Order number	122398 19,3
GTIN	4045197427342
Item class	12E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

Recommendation:

Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Through-coolant: no

Standard: DIN 6537 K

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth L_2 : 50.1 mm

Overall length L: 131 mm

Shank Ø D_s : 20 mm

Feed f in stainless steel < 900 N/mm²: 0.16 mm/rev.

Technical description

Shank tolerance	h6
Number of cutting edges Z	2
Flute length L_c	79 mm
Nominal Ø D_c	19.3 mm

Feed f in stainless steel < 900 N/mm ²	0.16 mm/rev.
Tolerance nominal Ø	m7
Shank Ø D _s	20 mm
Overall length L	131 mm
Standard	DIN 6537 K
recommended maximum drilling depth L ₂	50.1 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	no
Colour ring	blue
Type of product	Jobber drill