



Solid carbide high performance drill, Whistle-Notch shank DIN 6535 HE, TiAlN, Ø DC m7: 3 mm



Order data

Order number	122408 3
GTIN	4045197427373
Item class	12E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

Recommendation:

Maximum drilling depth:

clamping slot length (see table) less $1.5 \times$ nominal \varnothing .

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Through-coolant: yes, with 25 bar

Standard: DIN 6537 K

Tolerance nominal \varnothing : m7

Number of cutting edges Z: 2

Tolerance nominal \varnothing : m7

recommended maximum drilling depth L_2 : 15.5 mm

Overall length L: 62 mm

Shank $\varnothing D_s$: 6 mm

Feed f in stainless steel $< 900 \text{ N/mm}^2$: 0.07 mm/rev.

Technical description

Shank tolerance	h6
Number of cutting edges Z	2
Feed f in stainless steel $< 900 \text{ N/mm}^2$	0.07 mm/rev.
Nominal $\varnothing D_c$	3 mm

Flute length L_c	20 mm
Tolerance nominal \varnothing	m7
Shank $\varnothing D_s$	6 mm
Overall length L	62 mm
Standard	DIN 6537 K
recommended maximum drilling depth L_2	15.5 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	yes, with 25 bar
Colour ring	blue
Type of product	Jobber drill