

**HOLEX**
**Solid carbide high performance drill, Whistle-Notch shank DIN 6535 HE,  
TiAlN, Ø DC m7: 8,4 mm**

**Order data**

Order number	122408 8,4
GTIN	4045197427915
Item class	12E

**Description**
**Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

**Recommendation:**
**Maximum drilling depth:**

clamping slot length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Through-coolant: yes, with 25 bar

Standard: DIN 6537 K

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth  $L_2$ : 34.4 mm

Overall length L: 89 mm

Shank Ø  $D_s$ : 10 mm

Feed f in stainless steel < 900 N/mm<sup>2</sup>: 0.1 mm/rev.

**Technical description**

Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.1 mm/rev.
Flute length $L_c$	47 mm
Nominal Ø $D_c$	8.4 mm
Shank tolerance	h6

Number of cutting edges Z	2
Tolerance nominal $\varnothing$	m7
Shank $\varnothing D_s$	10 mm
Overall length L	89 mm
Standard	DIN 6537 K
recommended maximum drilling depth $L_2$	34.4 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	yes, with 25 bar
Colour ring	blue
Type of product	Jobber drill