

## Garant

### GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 19,5 mm



#### Order data

Order number	122415 19,5
GTIN	4045197785015
Item class	11E

#### Description

##### Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low power output** and high speeds.

- **Clear reduction in cutting forces due to special cutter geometry.**
- **Coating for best wear resistance even at high process temperatures.**
- **Polished flutes for good chip clearance.**

A **slim chisel edge** and the **special arrangement of the 4 guide chamfers** ensure **high positioning and alignment accuracy**. Optimised micro-geometry for increased working life and performance capability.

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122416**.

Form **HE**: order with **No. 122415 + 129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 49.8 mm

Overall length L: 131 mm

Shank Ø  $D_s$ : 20 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.38 mm/rev.

## Technical description

Shank $\varnothing D_s$	20 mm
Tolerance nominal $\varnothing$	h7
Number of cutting edges Z	2
Shank tolerance	h6
Nominal $\varnothing D_c$	19.5 mm
Feed f in steel < 1100 N/mm <sup>2</sup>	0.38 mm/rev.
Standard	DIN 6537 K
Flute length $L_c$	79 mm
Overall length L	131 mm
recommended maximum drilling depth $L_2$	49.8 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	solid carbide
Drill depth up to	4xD
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
------------------------	-----------