

Garant

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 2,2 mm



Order data

Order number	122415 2,2
GTIN	4045197783738
Item class	11E

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low power output** and high speeds.

- **Clear reduction in cutting forces due to special cutter geometry.**
- **Coating for best wear resistance even at high process temperatures.**
- **Polished flutes for good chip clearance.**

A **slim chisel edge** and the **special arrangement of the 4 guide chamfers** ensure **high positioning and alignment accuracy**. Optimised micro-geometry for increased working life and performance capability.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122416**.

Form **HE**: order with **No. 122415 + 129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 16.7 mm

Overall length L: 55 mm

Shank Ø D_s : 4 mm

Feed f in steel < 1100 N/mm²: 0.09 mm/rev.

Technical description

Shank $\varnothing D_s$	4 mm
Tolerance nominal \varnothing	h7
Shank tolerance	h6
Number of cutting edges Z	2
Standard	DIN 6537 K
Feed f in steel < 1100 N/mm ²	0.09 mm/rev.
Flute length L _c	20 mm
Nominal $\varnothing D_c$	2.2 mm
Overall length L	55 mm
recommended maximum drilling depth L ₂	16.7 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	solid carbide
Drill depth up to	4×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill