

## Garant

**GARANT Master Steel SPEED solid carbide drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 13,5 mm**



### Order data

Order number	122426 13,5
GTIN	4045197792198
Item class	11E

### Description

#### Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- **Clear reduction in cutting forces due to special cutter geometry.**
- **Coating for best wear resistance even at high process temperatures.**
- **Polished flutes for good chip clearance.**

A **slim chisel point** and the **special arrangement of the 4 guide chamfers** ensure **high positioning and alignment accuracy**. Optimised micro-geometry for increased working life and performance capability.

#### Recommendation:

#### Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 39.8 mm

Overall length L: 107 mm

Shank Ø  $D_s$ : 14 mm

Feed  $f$  in steel < 1100 N/mm<sup>2</sup>: 0.31 mm/rev.

### Technical description

Number of cutting edges Z	2
---------------------------	---

Feed f in steel < 1100 N/mm <sup>2</sup>	0.31 mm/rev.
Shank Ø D <sub>s</sub>	14 mm
Flute length L <sub>c</sub>	60 mm
Overall length L	107 mm
Nominal Ø D <sub>c</sub>	13.5 mm
Tolerance nominal Ø	h7
Standard	DIN 6537 K
Shank tolerance	h6
recommended maximum drilling depth L <sub>2</sub>	39.8 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	solid carbide
Drill depth up to	4×D
Point angle	135 degrees
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill