

## Garant

**Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø DC m6: 11,8 mm**



### Order data

|              |               |
|--------------|---------------|
| Order number | 122432 11,8   |
| GTIN         | 4045197539991 |
| Item class   | 11E           |

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. Excellent chip evacuation due to **4 internal coolant channels**. **Straight cutting edges** with honed edges and special flute profile for **short chips**. **Special coating** for the **best tool life** and **high metal removal rates**.

#### Recommendation:

##### Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ -

Standard: DIN 6537 K

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Tolerance nominal Ø: m6

recommended maximum drilling depth  $L_2$ : 37.3 mm

Overall length L: 102 mm

Shank Ø  $D_s$ : 12 mm

Feed f in Inconel®: 0.12 mm/rev.

### Technical description

|                           |              |
|---------------------------|--------------|
| Feed f in Inconel®        | 0.12 mm/rev. |
| Flute length $L_c$        | 55 mm        |
| Number of cutting edges Z | 2            |
| Nominal Ø $D_c$           | 11.8 mm      |

|  |                   |
|--|-------------------|
| Shank tolerance                          | h6                |
| Tolerance nominal $\varnothing$          | m6                |
| Shank $\varnothing D_s$                  | 12 mm             |
| Overall length L                         | 102 mm            |
| Standard                                 | DIN 6537 K        |
| recommended maximum drilling depth $L_2$ | 37.3 mm           |
| Coating                                  | TiAlN             |
| Tool material                            | Solid carbide     |
| Drill depth up to                        | 4xD               |
| Point angle                              | 140 degrees       |
| Shank                                    | DIN 6535 HB to h6 |
| Through-coolant                          | yes, with 25 bar  |
| Machining strategy                       | HPC               |
| Semi-Standard                            | yes               |
| Colour ring                              | pink              |
| Type of product                          | Jobber drill      |