

# GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 11,4 mm or inch



## **Order data**

Order number	122435 11,4
GTIN	4045197787194
Item class	11E

# **Description**

#### **Version:**

**3-flute drill**, specially developed for **use at very high feed rates**. Extremely suitable for **machines with high power** output and stable machining conditions.

- Special point geometry with stable cutting edges and large clearance at the centre permits very high feed rates.
- The patented point geometry is optimised for chip flow and generates low cutting forces with good chip breakage.
- · With 145° point angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel point guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

#### **Recommendation:**

### **Maximum drilling depth:**

flute length (see table) less 1.5 $\times$ nominal  $\varnothing$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

HB and HE shanks are available at the same price as HA.<br/>
Start Branks: use order No.

**122436**.<br/>br>For **HE shanks:** use order **No. 122435** + **129100HE**.

Machining strategy: HPC Standard: DIN 6537 K Tolerance nominal Ø: h7 Number of cutting edges Z: 3

Semi-Standard: yes Tolerance nominal Ø: h7

recommended maximum drilling depth L<sub>2</sub>: 37.9 mm

Overall length L: 102 mm Shank Ø D.: 12 mm Feed f in steel < 1100 N/mm<sup>2</sup>: 0.5 mm/rev.

# **Technical description**

Feed f in steel < 1100 N/mm <sup>2</sup>	0.5 mm/rev.
Standard	DIN 6537 K
Overall length L	102 mm
Flute length L <sub>c</sub>	55 mm
Shank Ø D <sub>s</sub>	12 mm
Tolerance nominal Ø	h7
Nominal Ø D <sub>c</sub>	11.4 mm
Number of cutting edges Z	3
recommended maximum drilling depth L <sub>2</sub>	37.9 mm
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	4×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

# **Services**

Shank grinding Type HE 129100 HE