

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 11 mm or inch



Order data

| Order number | 122435 11 |
|--------------|---------------|
| GTIN | 4045197787156 |
| Item class | 11E |

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Extremely suitable for **machines with high power** output and stable machining conditions.

- Special point geometry with stable cutting edges and large clearance at the centre permits very high feed rates.
- The patented point geometry is optimised for chip flow and generates low cutting forces with good chip breakage.
- · With 145° point angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel point guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5 \times nominal \varnothing .

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

HB and HE shanks are available at the same price as HA.

Start Branks: use order No.

122436.
br>For **HE shanks:** use order **No. 122435** + **129100HE**.

Machining strategy: HPC Standard: DIN 6537 K Tolerance nominal Ø: h7 Number of cutting edges Z: 3

Semi-Standard: yes Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 38.5 mm

Overall length L: 102 mm Shank Ø D_c: 12 mm Feed f in steel < 1100 N/mm²: 0.5 mm/rev.

Technical description

| Flute length L _c | 55 mm |
|---|---------------------|
| Shank Ø D _s | 12 mm |
| Nominal Ø D _c | 11 mm |
| Feed f in steel < 1100 N/mm ² | 0.5 mm/rev. |
| Number of cutting edges Z | 3 |
| Overall length L | 102 mm |
| Tolerance nominal Ø | h7 |
| Standard | DIN 6537 K |
| recommended maximum drilling depth L ₂ | 38.5 mm |
| Semi-Standard | yes |
| Series | GARANT Master Steel |
| Coating | TiAIN |
| Tool material | solid carbide |
| Drill depth up to | 4×D |
| Point angle | 145 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | Jobber drill |
| | |

Services

Shank grinding Type HE 129100 HE