

# GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7 (mm or inch): 4,5 mm or inch



### **Order data**

| Order number | 122435 4,5    |
|--------------|---------------|
| GTIN         | 4045197786500 |
| Item class   | 11E           |

## **Description**

#### **Version:**

**3-flute drill**, specially developed for **use at very high feed rates**. Extremely suitable for **machines with high power** output and stable machining conditions.

- Special point geometry with stable cutting edges and large clearance at the centre permits very high feed rates.
- The patented point geometry is optimised for chip flow and generates low cutting forces with good chip breakage.
- · With 145° point angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel point guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

#### **Recommendation:**

#### Maximum drilling depth:

flute length (see table) less 1.5 $\times$ nominal  $\varnothing$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

HB and HE shanks are available at the same price as HA.<br/>
Strain HB shanks: use order No.

**122436**.<br/>br>For **HE shanks:** use order **No. 122435 + 129100HE**.

Standard: DIN 6537 K Tolerance nominal Ø: h7 Number of cutting edges Z: 3 Tolerance nominal Ø: h7

recommended maximum drilling depth L<sub>2</sub>: 17.3 mm

Overall length L: 66 mm Shank Ø D<sub>s</sub>: 6 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.28 mm/rev.

# **Technical description**

| Shank Ø D <sub>s</sub>                   | 6 mm                |
|--|---------------------|
| Flute length L <sub>c</sub>              | 24 mm               |
| Nominal Ø D <sub>c</sub>                 | 4.5 mm              |
| Number of cutting edges Z                | 3                   |
| Feed f in steel < 1100 N/mm <sup>2</sup> | 0.28 mm/rev.        |
| Overall length L                         | 66 mm               |
| Standard                                 | DIN 6537 K          |
| Tolerance nominal Ø                      | h7                  |
| recommended maximum drilling depth $L_2$ | 17.3 mm             |
| Series                                   | GARANT Master Steel |
| Coating                                  | TiAIN               |
| Tool material                            | solid carbide       |
| Drill depth up to                        | 4×D                 |
| Point angle                              | 145 degrees         |
| Shank                                    | DIN 6535 HA to h6   |
| Through-coolant                          | yes, with 25 bar    |
| Machining strategy                       | HPC                 |
| Semi-Standard                            | yes                 |
| Colour ring                              | green               |
| Type of product                          | Jobber drill        |

# Services

| Shank grinding Type HE | 129100 HE |
|------------------------|-----------|
|------------------------|-----------|