Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7 (mm or inch): 5 mm or inch



Order data

Order number	122435 5
GTIN	4045197786555
Item class	11E

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Extremely suitable for **machines with high power** output and stable machining conditions.

- Special point geometry with stable cutting edges and large clearance at the centre permits very high feed rates.
- The patented point geometry is optimised for chip flow and generates low cutting forces with good chip breakage.
- With 145° point angle for low burr formation when drilling through holes.
- The sector-leading technology of the chisel point guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

HB and HE shanks are available at the same price as HA.
For **HB shanks:** use order **No. 122436**.
For **HE shanks:** use order **No. 122435** + **129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 3

Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 20.5 mm

Overall length L: 66 mm

Shank Ø D_s: 6 mm

Feed f in steel < 1100 N/mm²: 0.28 mm/rev.

Technical description

5 mm
6 mm
h7
3
66 mm
DIN 6537 K
28 mm
0.28 mm/rev.
20.5 mm
GARANT Master Steel
TiAIN
solid carbide
4×D
145 degrees
DIN 6535 HA to h6
yes, with 25 bar
HPC
yes
green
Jobber drill

Services

Shank grinding	Type HE
----------------	---------

129100 HE